

Zoë-CM2[™] Culture Module

Zoë sustains the life of cells within Emulate Organ-Chips by automating the precise microphysiological conditions needed to culture up to 12 chips. As an open platform, Zoë enables researchers to build a wide variety of organ models for myriad applications—from disease modeling, to target validation, to drug candidate safety and efficacy evaluation.



Key Functionality



Seamless Interface

Avoid complex, manual, and error-prone syringe pump and tubing setups with an integrated platform.



Media Flow

Independently control the flow rate in each channel or establish an air-liquid interface, depending on experimental needs.



Cyclic Stretch

Adjust the frequency and strain of cyclic stretch to recreate the mechanical forces of breathing or peristalsis.



Bubble Reduction

Overcome a point of failure common in other microphysiological systems with the proprietary Regulate™ Cycle



Auditable Data Log

Easily audit historical pressure and stretch performance with automatically generated data logs.



Part of the Human Emulation System®

Zoë-CM2 is part of the Human Emulation System®a complete Organ-on-a-Chip solution that includes instruments, consumables, and software applications.

The Human Emulation System is designed to make Organ-on-a-Chip technology reliable and accessible for researchers of any experience level, enabling more reproducible, physiologically relevant studies across a variety of organ models and applications.



Zoë-CM2 Specifications:

General

Overall Size 178 x 218 x 429 mm

 $(7.0" \times 8.6" \times 16.9")$

Weight

10.9 kg (24 lbs)

Power Consumption

13W

Operating Requirements

Instrument Rating 24 VDC, 3.5 A, 50-60 Hz

Gas Input Pressure 276 kPa + / - 35 (40 psig + / - 5)

Gas Input Composition 5% CO₂, balance air

-70 kPa (-10.2 psig), minimum Vacuum Input Pressure

Environmental

Operating Temperature 20-38 °C

> 0-95% Relative Humidity

> > Max Altitude 2.000 meters

Flow Range $0 \mu L / h$, or $10-1,000 \mu L / h + / - 10%*$

0-12% Stretch Range

Stretch Frequency 0.0-0.40 Hz

To learn more and order, visit emulatebio.com/zoe

^{*}Flow tolerances may vary. Tolerance is based on Zoë-CM2 with firmware 1.3.0 or above.